



AMERICAN WIRE ROPE COMPANY

Read important warnings and information in T.O.C. > GENERAL WARNINGS and WIRE ROPE


Bright and Drawn Galvanized Wire Rope 6 X 19 Class and 6 X 36 Class

According to Federal Specification RR-W-410E. Meets the performance requirements of API-9A, and A.S.T.M. A1023/1023M Wire Rope for General Purposes, as applicable. Preformed, right regular lay. Other lays are available for certain sizes and constructions, such as RAL, LAL, LRL, and lang lay. EEIPS grade ropes are also available upon request and stocked on several items.


FIBER CORE (EIPS)		
Diameter in Inches	Approx. Weight per foot in Pounds	Breaking Strength in Tons*
5/16	.164	4.69
3/8	.236	6.71
7/16	.32	9.10
1/2	.42	11.80
9/16	.53	14.90
5/8	.66	18.40
3/4	.95	26.20
7/8	1.29	35.40
1	1.68	46.00
1.1/8	2.13	57.90
1.1/4	2.63	71.10

IWRC (EIPS)		
Diameter in Inches	Approx. Weight per foot in Pounds	Breaking Strength in Tons*
1/4	.116	3.40
5/16	.18	5.27
3/8	.26	7.55
7/16	.35	10.20
1/2	.46	13.30
9/16	.59	16.80
5/8	.72	20.60
3/4	1.04	29.40
7/8	1.42	39.80
1	1.85	51.70
1.1/8	2.34	65.00
1.1/4	2.89	79.90
1.3/8	3.50	96.00
1.1/2	4.16	114.00
1.5/8	4.88	132.00
1.3/4	5.67	153.00


*Listed for comparison only. Actual operating loads may vary, but should never exceed the recommended design factor or 20% of catalog Breaking Strength.




6 X 19 SEALE WITH IWRC




6 X 25 FILLER WIRE WITH IWRC



6 X 26 WARRINGTON SEALE WITH IWRC



6 X 31 WARRINGTON SEALE WITH IWRC



6 X 36 WARRINGTON SEALE WITH IWRC

