



CHAIN ASSEMBLIES

Read important warnings and information in T.O.C. > GENERAL WARNINGS and CHAIN ⚠️
**CAUTION: NEVER EXCEED THE WORKING LOAD LIMIT.
DO NOT USE FOR OVERHEAD LIFTING OR WHERE ITS FAILURE WILL CAUSE
DAMAGE TO PROPERTY OR LIFE.**

HIGH TEST BOOMER CHAIN (GRADE 43)

High Test chain with grab hook each end.



Size	Working Load Limit in Pounds	Approx. Wt. Each in Pounds
1/4" x 20 ft.	2,600	13.5
5/16" x 20 ft.	3,900	20.0
3/8" x 20 ft.	5,400	30.5

BINDING CHAIN (GRADE 70)

Transport chain with grab hook each end.



Size	Working Load Limit in Pounds	Approx. Wt. Each in Pounds
5/16" x 20 ft.	4,700	20.0
3/8" x 20 ft.	6,600	30.0
1/2" x 20 ft.	11,300	52.4

TAIL CHAIN (WINCH LINE END CHAIN) - DOMESTIC

Use same size chain as wire rope.

Wire Rope Diam.	Length	Working Load Limit in Pounds	Grade	No. of Links	Approx. Weight Each in Pounds
3/8"	18"	5,400	High Test	13	5
1/2"	18"	9,200	High Test	7	9
5/8"	18"	18,100	Alloy	8	10
3/4"	18"	28,300	Alloy	9	13
7/8"	24"	34,200	Alloy	9	24
1"	24"	47,700	Alloy	7	27

Proper end connection to wire rope should be maintained.



CLEVIS TYPE J HOOKS - DOMESTIC

Zinc Plated

Size	Working Load Limit in Pounds	Weight Each in Pounds
8"	3,000	2.03
15"	3,000	3.14