



CHAIN - HIGH TEST CHAIN GRADE 43

Read important warnings and information in T.O.C. > GENERAL WARNINGS and CHAIN ⚠️
**CAUTION: NEVER EXCEED THE WORKING LOAD LIMIT OF CHAIN.
NEVER USE GRADE 43, HIGH TEST CHAIN FOR OVERHEAD LIFTING OR
WHERE ITS FAILURE WILL CAUSE DAMAGE TO PROPERTY OR LIFE.**

According to ASTM A413 and NACM Specification.
Proof tested to 2x the Working Load Limit.

HIGH TEST CHAIN (GRADE 43)

Bright or hot galvanized.

Nominal Size mm	Nominal Size inches	Working Load Limit in Pounds	Feet per Drum	Ft. per 1/2 Drum	Minimum Weight per Foot	Max. Length per 100 links
7.0	1/4"	2,600	800	400	.63	124.0"
8.0	5/16"	3,900	550	275	.93	129.1"
10.0	3/8"	5,400	400	200	1.41	137.8"
13.0	1/2"	9,200	200	100	2.4	179.1"
16.0	5/8"	13,000	150	75	3.58	220.5"
20.0	3/4"	20,200	100	50	5.48	275.6"

DEALER PAILS, HIGH TEST CHAIN (GRADE 43)

Bright.

Nominal Size mm	Nominal Size inches	Working Load Limit in Pounds	Feet per Pail, approx.
7.0	1/4"	2,600	130
8.0	5/16"	3,900	90
10.0	3/8"	5,400	64