



## CHAIN - PROOF COIL CHAIN GRADE 30

Read important warnings and information in T.O.C. > GENERAL WARNINGS and CHAIN ⚠️  
**CAUTION: NEVER EXCEED THE WORKING LOAD LIMIT OF CHAIN.  
 NEVER USE PROOF COIL CHAIN FOR OVERHEAD LIFTING OR WHERE ITS  
 FAILURE WILL CAUSE DAMAGE TO PROPERTY OR LIFE.**

### PROOF COIL CHAIN (GRADE 30)

Bright, zinc plated or hot galvanized. According to ASTM A413 and NACM Specification.

Proof tested to 2x the Working Load Limit.

Nominal Size mm	Nominal Size inches	Working Load Limit in Pounds	Feet per Drum	Ft. per 1/2 Drum	Minimum Weight per Foot	Max. Length per 100 links
4	1/8"	400	—	1,000	.17	90.5"
5.5	3/16"	800	1600	800	.33	96.4"
7	1/4"	1,300	800	400	.63	124.0"
8	5/16"	1,900	550	275	.93	129.1"
10	3/8"	2,650	400	200	1.41	137.8"
13	1/2"	4,500	200	100	2.40	179.1"
16	5/8"	6,900	150	75	3.58	220.5"
20	3/4"	10,600	100	50	5.48	275.6"
22	7/8"	12,800	75	35	7.31	258.7"
26	1"	17,900	60	30	9.41	287.8"

### DEALER PAILS, PROOF COIL CHAIN (GRADE 30)

Bright, zinc plated or hot galvanized. According to ASTM A413 and NACM Specification.

Proof tested to 2x the Working Load Limit.

Nominal Size mm	Nominal Size inches	Working Load Limit in Pounds	Feet per Pail, approx.
4	1/8"	400	500
5.5	3/16"	800	250
7	1/4"	1,300	141
8	5/16"	1,900	92
10	3/8"	2,650	63
13	1/2"	4,500	35

### LONG LINK CHAIN (GRADE 30) - BUMPER MOORING CHAIN

Hot galvanized

Nominal Size mm	Nominal Size inches	Working Load Limit in Pounds	Feet per Drum	Inside Length*	Inside Width*	Min. Weight per Foot in Pounds
13	1/2"	4,500	200	3.15	.94	2.22
16	5/8"	6,900	150	2.52	.96	3.41
20	3/4"	10,600	100	2.94	1.10	4.20

\* ± 4%