



CHAIN - TRANSPORT CHAIN GRADE 70

Read important warnings and information in T.O.C. > GENERAL WARNINGS and CHAIN ⚠️
**CAUTION: NEVER EXCEED THE WORKING LOAD LIMIT OF CHAIN.
 NEVER USE GRADE 70 CHAIN FOR OVERHEAD LIFTING OR WHERE ITS FAILURE WILL CAUSE DAMAGE TO PROPERTY OR LIFE.**

TRANSPORT CHAIN (GRADE 70) Plated

Yellow chromate finish. According to ASTM A413 and NACM Specification.

Proof tested to 2x the Working Load Limit.

Nominal Size mm	Nominal Size inches	Working Load Limit in Pounds	Feet per Drum	Ft. per 1/2 Drum	Minimum Weight per Foot in Pounds	Max. Length per 100 Links
7.0	1/4"	3,150	800	400	.63	124.0"
8.0	5/16"	4,700	550	275	.93	129.1"
10.0	3/8"	6,600	400	200	1.41	137.8"
13.0	1/2"	11,300	200	100	2.4	179.1"

Dealer Pails on request.

CHAIN - STAINLESS STEEL CHAIN, TYPE 316L

Read important warnings and information in T.O.C. > GENERAL WARNINGS and CHAIN
CAUTION: NEVER EXCEED THE WORKING LOAD LIMIT OF CHAIN.

STAINLESS STEEL CHAIN

Nominal Size mm	Nominal Size inches	*Working Load Limit in Pounds*	Feet per Drum	Minimum Weight per Foot in Pounds	Max. Length per 100 Links
4.0	1/8"	620	1000	.17	88.8"
5.0	3/16"	930	1000	.38	96.4"
7.0	1/4"	1,570	800	.61	124.0"
8.0	5/16"	2,400	550	.84	129.1"
10.0	3/8"	3,550	400	1.4	137.8"
13.0	1/2"	6,500	200	2.34	179.1"
16.0	5/8"	9,800	300	3.58	220.5"
19.5	3/4"	15,000	200	5.51	275.6"

*AT ROOM TEMPERATURE