





KULKONI / *CM MIDLAND* DOMESTIC FITTINGS



RIGGING EYE HOOK AND LATCH - CARBON - ALLOY (LATCH SEPARATE)

* Alloy Swivel hooks assembled with latch also available

WLL		Dimensions in Inches										Approx weight per 100 (lbs.)
CRG	ALY	A	B	C	D	E	G	H	K	L	R	
3/4	1	1.500	.750	.375	3.000	1.000	.750	.875	.562	4.375	3.125	63
1	1.1/2	1.75	.875	4.38	3.188	1.078	.844	.938	.625	4.938	3.656	85
1.1/2	2	2.125	1.125	.500	3.625	1.125	1.00	1.156	.750	5.594	4.094	138
2	3	2.500	1.25	.625	4.094	1.250	1.125	1.312	.844	6.438	4.688	192
3	5	3.063	1.563	.750	5.063	1.531	1.438	1.625	1.125	7.969	5.781	370
5	7	3.875	2.000	.938	6.500	1.969	1.875	2.063	1.375	10.125	7.313	728
7.1/2	11	4.685	2.441	1.122	7.598	2.244	2.480	2.606	1.850	12.500	9.055	687
11	15	5.354	2.835	1.268	8.700	2.480	2.756	2.917	2.165	13.984	10.039	993
15	22	6.614	3.504	1.555	11.102	3.346	3.228	3.516	2.598	17.126	12.480	1683

Latch is designed to retain such items as slings and chains under slack conditions. The latch is not intended to support the load. (11 Ton Alloy Hook & Latch are old style)

CAUTION: NEVER EXCEED WORKING LOAD LIMITS