



SYNTHETIC ROPE

Read important warnings and information in T.O.C. > GENERAL WARNINGS and CORDAGE ⚠️.
Breaking Strength is listed for comparison only. Never exceed the Working Load Limit.



NYLON ROPE 3-STRAND, TWISTED, SOFT-LAY, WHITE.

Nominal Diameter	Nominal Circumference	Feet per Reel/Coil	Working Load Limit in Pounds	Breaking Strength in Pounds	Approx. Net Weight per Reel in Pounds *
1/4"	3/4"	600	124	1,485	9
1/4"	3/4"	1,200	124	1,485	18
5/16"	1"	600	192	2,250	15
5/16"	1"	1,200	192	2,250	30
3/8"	1.1/8"	600	278	3,330	21
1/2"	1.1/2"	600	525	5,760	39
1/2"	1.1/2"	1,200	525	5,760	78
5/8"	2"	600	935	9,360	63
3/4"	2.1/4"	600	1,420	12,750	87
3/4"	2.1/4"	1,200	1,420	12,750	174
7/8"	2.3/4"	600	2,000	18,000	120
1"	3"	600	2,520	22,500	158
1.1/4"	3.3/4"	600	3,760	33,750	240
1.1/2"	4.1/2"	600	5,320	47,700	330

* Weights may vary + or - 5%

POLYPROPYLENE ROPE, 3-STRAND, TWISTED, YELLOW.

Nominal Diameter	Nominal Circumference	Feet per Reel/Coil	Working Load Limit in Pounds	Breaking Strength in Pounds	Approx. Net Weight per Reel in Pounds
1/4"	3/4"	600	113	1,130	7.2
1/4"	3/4"	1,200	113	1,130	14.4
1/4"	3/4"	4,000	113	1,130	48
5/16"	1"	600	171	1,710	10.8
5/16"	1"	1,200	171	1,710	21.6
3/8"	1.1/8"	600	244	2,440	16.8
3/8"	1.1/8"	1,200	244	2,440	33.6
1/2"	1.1/2"	600	420	3,780	28.2
1/2"	1.1/2"	1,200	420	3,780	56.4
5/8"	2"	600	700	5,600	45
5/8"	2"	1,200	700	5,600	90
3/4"	2.1/4"	600	1,090	7,650	64.2
3/4"	2.1/4"	1,200	1,090	7,650	128.4
7/8"	2.3/4"	600	1,490	10,400	90
1"	3"	600	1,800	12,600	108
1.1/8"	3.1/2"	600	2,360	16,500	142.8



PURE MANILA ROPE

Read important warnings and information in T.O.C. > GENERAL WARNINGS and CORDAGE ⚠️.
Breaking Strength is listed for comparison only. Never exceed the Working Load Limit.



Nominal Diameter	Nominal Circumference	Feet per Coil	Working Load Limit in Pounds	Breaking Strength in Pounds	Approx. Net Weight per Reel in Pounds
1/4"	3/4"	600	54	540	12
1/4"	3/4"	1,250	54	540	25
1/4"	3/4"	2,500	54	540	50
5/16"	1"	1,725	90	900	50
3/8"	1.1/8"	600	122	1,220	24.6
3/8"	1.1/8"	1,200	122	1,220	49.2
7/16"	1.1/4"	600	176	1,580	31.5
1/2"	1.1/2"	600	264	2,380	45
1/2"	1.1/2"	1,200	264	2,380	90
5/8"	2"	600	496	3,960	79.8
5/8"	2"	1,200	496	3,960	159.6
3/4"	2.1/4"	600	695	4,860	100.2
3/4"	2.1/4"	1,200	695	4,860	200.4
13/16"	2.1/2"	600	835	5,850	117
7/8"	2.3/4"	600	995	6,950	134.4
1"	3"	600	1,160	8,100	162
1"	3"	1,200	1,160	8,100	324
1.1/8"	3.1/2"	600	1,540	10,800	216
1.1/8"	3.1/2"	300	1,540	10,800	108
1.1/8"	3.1/2"	350	1,540	10,800	126
1.1/4"	3.3/4"	600	1,740	12,200	249.6
1.1/4"	3.3/4"	300	1,740	12,200	124.8
1.1/4"	3.3/4"	350	1,740	12,200	145.6
1.1/2"	4.1/2"	600	2,380	16,700	360
2"	6"	600	4,000	28,000	648

SISAL ROPE

3-STRAND

Uncoiled, clipped white sisal. Coiled in cartons.

Nominal Diameter	Nominal Circumference	Weight per Carton in Pounds	Feet per Carton (Approx)	Working Load Limit in Pounds	Breaking Strength in Pounds
3/16"	5/8"	50	3,300	36	360
1/4"	3/4"	50	2,500	48	480
5/16"	1"	50	1,725	80	800
3/8"	1.1/8"	50	1,220	108	1,080
7/16"	1.1/4"	50	950	156	1,400
1/2"	1.1/2"	50	665	236	2,120
5/8"	2"	80	600	440	3,520
3/4"	2.1/4"	100	600	617	4,320