




IMPORTED and DOMESTIC LINKS—GRADE 100

CAUTION: NEVER EXCEED THE WORKING LOAD LIMIT.
Read important warnings and information in T.O.C. > GENERAL WARNINGS and LINKS ⚠️.

GRADE 100 SUB ASSEMBLY, ALLOY

Grade 100 alloy, heat treated. Painted. Meets the performance requirements of ASTM A952




Dimensions in Inches								Approximate Weight Each in Pounds
Size	Chain Size	A	B	C	D	E	F	
3/4"	9/32"	0.75	2.95	5.31	0.50	0.98	2.13	2.65
7/8"	5/16"	0.88	3.62	6.50	0.63	1.34	2.76	5.07
1"	3/8"	1.00	3.94	7.09	0.75	1.57	3.35	7.85
1.1/4"	1/2"	1.25	4.33	7.87	0.88	1.97	4.53	13.34
1.1/2"	5/8"	1.50	5.51	10.24	1.00	2.56	5.51	22.05

GRADE 100 ALLOY FITTINGS

CAUTION: NEVER EXCEED THE WORKING LOAD LIMIT.
Read important warnings and information in T.O.C. > GENERAL WARNINGS and LINKS ⚠️.

GRADE 100 SELF LOCKING CLEVIS HOOK


Grade 100 alloy, heat treated. Painted. Meets the performance requirements of ASTM A952



Dimensions in Inches								Approximate Weight Each in Pounds
Size	W.L.L. in lbs.	A	B	C	D	E	F	
9/32	4,300	1.34	0.35	0.39	0.35 x 0.89	4.84	1.69	2.09
5/16"	5,700	1.34	0.35	0.39	0.39 x 0.89	4.84	1.69	2.09
3/8"	8,800	1.77	0.47	0.55	0.51 x 1.24	5.63	2.20	3.53
1/2"	15,000	2.01	0.59	0.67	0.63 x 1.65	7.09	2.72	7.05
5/8"	22,600	2.36	0.75	0.75	0.82 x 2.03	8.46	3.15	13.23
3/4"	35,300	2.76	0.91	1.02	0.94 x 2.87	9.96	3.54	21.61

GRADE 100 SELF LOCKING EYE HOOK

Grade 100 alloy, heat treated. Painted. Meets the performance requirements of ASTM A952



Dimensions in Inches							Approximate Weight Each in Pounds
Size	W.L.L. in lbs.	A	B	C	D	E	
9/32-5/16"	5,700	1.34	0.47	0.98	5.31	1.69	2.12
3/8"	8,800	1.77	0.63	1.30	6.61	2.20	3.64
1/2"	15,000	2.01	0.79	1.57	8.07	2.72	7.16
5/8"	22,600	2.36	1.06	1.97	9.88	3.15	13.45
3/4"	35,300	2.76	1.18	2.36	11.42	3.54	21.61