




CHAIN HOOKS

CAUTION: NEVER EXCEED THE WORKING LOAD LIMIT.
 Read important warnings and information in T.O.C. > GENERAL WARNINGS and HOOKS ⚠️.

HIGH TEST* CLEVIS GRAB HOOKS, GRADE 43

Forged steel, heat treated, plated.

DO NOT USE FOR OVERHEAD LIFTING




Size	Working Load Limit	Approximate Weight Each	Dimension in Inches			
	in Pounds	in Pounds	A	B	C	D
1/4"	2,600	0.43	0.38	0.38	0.34	1.94
5/16"	3,900	0.72	0.44	0.44	0.41	2.38
3/8"	5,400	1.15	0.56	0.47	0.50	2.63
1/2"	9,200	2.35	0.69	0.63	0.66	3.50
5/8"	13,000	4.10	0.81	0.63	0.81	4.19

Also available in DOMESTIC. * Ultimate Load is 3 times the Working Load Limit.

HIGH TEST* CLEVIS SLIP HOOKS, GRADE 43

Forged steel, heat treated, plated.

DO NOT USE FOR OVERHEAD LIFTING




Size	Working Load Limit	Approximate Weight Each	Dimension in Inches			
	in Pounds	in Pounds	A	B	C	D
1/4"	2,600	0.58	0.38	0.38	0.88	2.56
5/16"	3,900	0.86	0.44	0.44	1.00	2.81
3/8"	5,400	1.40	0.56	0.47	1.28	3.25
1/2"	9,200	2.20	0.63	0.56	1.38	4.00

* Ultimate Load is 3 times the Working Load Limit.

HIGH TEST* EYE GRAB HOOKS, GRADE 43

Forged steel, heat treated, plated.

DO NOT USE FOR OVERHEAD LIFTING




Size	Working Load Limit	Approximate Weight Each	Dimension in Inches			
	in Pounds	in Pounds	A	B	C	D
1/4"	2,600	0.30	0.50		0.31	1.88
5/16"	3,900	0.57	0.56		0.44	2.25
3/8"	5,400	0.95	0.69		0.50	2.56
1/2"	9,200	2.14	0.88		0.59	3.50

* Ultimate Load is 3 times the Working Load Limit.

HIGH TEST* EYE SLIP HOOKS, GRADE 43

Forged steel, heat treated, plated.

DO NOT USE FOR OVERHEAD LIFTING




Size	Working Load Limit	Approximate Weight Each	Dimension in Inches			
	in Pounds	in Pounds	A	B	C	D
1/4"	2,600	0.36	0.50		0.69	2.00
5/16"	3,900	0.60	0.75		1.00	2.56
3/8"	5,400	0.91	0.75		1.06	3.00
1/2"	9,200	1.94	1.06		1.38	4.13

* Ultimate Load is 3 times the Working Load Limit.

ALLOY* CLEVIS GRAB HOOKS

Forged steel, heat treated, painted.

DO NOT USE FOR OVERHEAD LIFTING




Size	Working Load Limit	Approximate Weight Each	Dimension in Inches			
	in Pounds	in Pounds	A	B	C	D
1/4"	3,500	0.43	0.38	0.38	0.34	1.94
5/16"	4,500	0.72	0.44	0.44	0.41	2.38
3/8"	7,100	1.15	0.56	0.47	0.50	2.63
1/2"	12,000	2.35	0.69	0.63	0.66	3.50

* Ultimate Load is 4 times the Working Load Limit.

ALLOY* CLEVIS SLIP HOOKS

Forged steel, heat treated, plated.

DO NOT USE FOR OVERHEAD LIFTING



Size	Working Load Limit	Approximate Weight Each	Dimension in Inches			
	in Pounds	in Pounds	A	B	C	D
1/4"	2,750	0.58	0.38	0.38	0.88	2.56
5/16"	4,300	0.86	0.44	0.44	1.00	2.81
3/8"	5,250	1.40	0.56	0.47	1.28	3.25
1/2"	9,000	2.20	0.63	0.56	1.38	4.00

* Ultimate Load is 4 times the Working Load Limit.