




IMPORTED and DOMESTIC LINKS

CAUTION: NEVER EXCEED THE WORKING LOAD LIMIT.
Read important warnings and information in T.O.C. > GENERAL WARNINGS and LINKS ⚠️.

GRADE 80 SUB ASSEMBLY, ALLOY

Grade 80 alloy, heat treated. Painted. Meets the performance requirements of ASTM A952




Dimensions in Inches								Approximate Weight Each in Pounds
Size	Chain Size	A	B	C	D	E	F	
3/4"	9/32"	.80	3.75	6.30	.50	2.36	4.33	4.7
1"	3/8"	1.05	4.33	7.50	.75	3.75	6.30	11.4
1.1/4"	1/2"	1.27	5.10	9.00	1.00	4.33	7.50	20.3
1.1/2"	5/8"	1.50	5.90	10.80	1.13	5.10	9.05	36.4
1.3/4"	3/4"	1.75	7.10	13.40	1.25	5.10	9.05	54.0
2"	7/8"	2.00	7.50	13.75	1.50	6.00	11.90	90.0
2.1/4"	1"	2.25	7.90	15.75	1.75	7.10	13.80	129.0

GRADE 80 ALLOY FITTINGS

CAUTION: NEVER EXCEED THE WORKING LOAD LIMIT.
Read important warnings and information in T.O.C. > GENERAL WARNINGS and LINKS ⚠️.

GRADE 80 SELF LOCKING CLEVIS HOOK


Grade 80 alloy, heat treated. Painted. Meets the performance requirements of ASTM A952



Dimensions in Inches								Approximate Weight Each in Pounds
Size	W.L.L. in lbs.	A	B	C	D	E	F	
9/32-5/16"	4,500	1.09	.34	.43	.35	3.72	1.42	1.2
3/8"	7100	1.50	.48	.55	.51	4.92	1.81	2.6
1/2"	12000	1.81	.60	.69	.63	6.18	2.36	5.0
5/8"	18100	2.24	.75	.77	.82	7.44	2.95	9.0

GRADE 80 SELF LOCKING EYE HOOK

Grade 80 alloy, heat treated. Painted. Meets the performance requirements of ASTM A952



Dimensions in Inches							Approximate Weight Each in Pounds
Size	W.L.L. in lbs.	A	B	C	D	E	
9/32-5/16"	4,500	1.08	.39	1.02	4.43	1.42	1.2
3/8"	7,100	1.50	.51	1.30	5.94	1.81	2.5
1/2"	12,000	1.81	.63	1.65	7.28	2.36	4.9
5/8"	18,100	2.24	.71	2.05	9.05	2.95	8.8