



STAINLESS TURNBUCKLES

CAUTION: NEVER EXCEED THE WORKING LOAD LIMIT.


Read important warnings and information in T.O.C. > GENERAL WARNINGS and TURNBUCKLES ⚠️.



JAW & JAW



EYE & EYE



BODY



JAW & EYE

FORGED and CAST Stainless

Size	Working Load Limit in Pounds	Average Overall Length in Inches with Ends in Closed Position	Approximate Weight Each in Pounds		
			Eye & Eye	Jaw & Eye	Jaw & Jaw
1/4" x 4"	460	8.75	.30	.30	.40
5/16" x 4.1/2"	780	9.56	.50	.53	.58
3/8" x 6"	1,160	12.00	.75	.82	.93
1/2" x 6"	2,150	13.50	1.50	1.62	1.68
5/8" x 6"	3,500	15.50	2.63	2.69	2.82
3/4" x 6"	5,140	17.00	3.75	4.25	4.68
1" x 6" *	10,000	20.63	10.75	11.10	11.80
1" x 12" *	10,000	26.63	11.25	12.00	12.88
1.1/4" x 12" *	15,200	29.88	19.00	21.20	23.60

* Cast only 1" and larger.

GALVANIZED LOCKNUTS or JAMNUTS

FOR GALVANIZED TURNBUCKLES LEFT OR RIGHT THREAD

Sold in pairs only, 1 each R.H., 1 each L.H., galvanized

Size	Thread	Approximate Weight Each in Pounds	NC Threads per Inch	Width Across Flat (A) in Inches
3/8"	Left or right	.01	16	.56
1/2"	Left or right	.03	13	.75
5/8"	Left or right	.05	11	.94
3/4"	Left or right	.08	10	1.13
7/8"	Left or right	.11	9	1.31
1"	Left or right	.18	8	1.50
1.1/4"	Left or right	.37	7	1.81
1.1/2"	Left or right	.60	6	2.19
1.3/4"	Left or right	1.02	5	2.56
2"	Left or right	2.25	4.1/2	2.94
2.1/2"	Left or right	3.13	4	3.75
2.3/4"	Left or right	3.30	4	4.13



Do not over tighten locknuts during installation.