




VINYL COATED CABLE - GALVANIZED & STAINLESS

Read important warnings and information in T.O.C. > GENERAL WARNINGS and WIRE ROPE 


Small diameter 7 x 7 and 7 x 19 construction cable is sometimes referred to as "aircraft cable". **It is not intended for aircraft use** but designed for industrial and marine applications. When using wire rope clips with plastic coated cable, match clip size to uncoated cable diameter (3/16" cable coated to 1/4" takes 3/16" clip.) Strip plastic coating off cable where clips will be positioned for full holding power. Uncoated cable according to Federal Specification RR-W-410E. Uncoated galvanized cable is in accordance with A.S.T.M. A1023/1023M, Wire Rope for General Purposes, as applicable.

CLEAR VINYL COATED CABLE, GALVANIZED

Cable Diameter	Coated to	Approx. Wt. per 1000 Ft. in Pounds	Breaking Strength in Pounds*	Construction
1/16"	3/32"	9.3	480	7 x 7
1/16"	1/8"	11.8	480	7 x 7
3/32"	1/8"	18.5	920	7 x 7
3/32"	3/16"	25.8	920	7 x 7
1/8"	3/16"	35.2	1,700	7 x 7
1/4"	5/16"	122	6,100	7 x 7
3/32"	1/8"	19.9	1,000	7 x 19
1/8"	3/16"	36.2	2,000	7 x 19
3/16"	1/4"	77.5	4,200	7 x 19
3/16"	5/16"	77.5	4,200	7 x 19
1/4"	5/16"	123	7,000	7 x 19
5/16"	3/8"	197	9,800	7 x 19
3/8"	7/16"	270	14,400	7 x 19



7 x 7



7 x 19

DISPLAY REELS – Vinyl Coated Galvanized Cable


Cable Diameter	Coated to	Approx. Wt. per 1000 Ft. in Pounds	Construction	Lengths Available in ft.	
				500'	250'
3/32"	3/16"	25.8	7 x 7	500'	250'
1/8"	3/16"	35.2	7 x 7	500'	250'
3/16"	1/4"	77.5	7 x 19	500'	250'
1/4"	5/16"	123	7 x 19	500'	200'
5/16"	3/8"	197	7 x 19	500'	200'



DISPLAY REELS

CLEAR VINYL COATED STAINLESS CABLE TYPE 304

Cable Diameter	Coated to	Approx. Wt. per 1000 Ft. in Pounds	Breaking Strength in Pounds*	Construction
1/16"	3/32"	9.3	480	7 x 7
3/32"	1/8"	18.5	920	7 x 7
1/8"	3/16"	36.2	1,760	7 x 19
3/16"	1/4"	77.5	3,700	7 x 19
1/4"	5/16"	123	6,400	7 x 19
5/16"	3/8"	197	9,000	7 x 19
3/8"	7/16"	270	12,000	7 x 19



7 x 19

Also available on special order: nylon and vinyl in various colors. Approx. 10 days delivery.

* Listed for comparison only. Actual operating loads may vary, but should never exceed recommended design factor or 20% of catalog Breaking Strength.